

# C2425dw

Reliability. Security. Productivity.



C2425dw

We back this product with a guarantee that covers repair actions including the cost of spare parts in the first four years.\* The guarantee also offers you free 24hour self-help online support and access to technical support by phone during working hours.



\*Offer applies if the product is registered within 90 days from the date of purchase. Supplies and/or consumable parts, such as fuser or transfer unit, are excluded. Please refer to the detailed terms and conditions available at lexmark.com/myguarantee.

# Lexmark C2425dw

Start your colour journey with the Lexmark C2425dw, the printer that helps you control the cost of colour, with a print speed of up to 23 ppm<sup>\*</sup>. Built for reliability, performance and security, the Lexmark C2425dw comes equipped with built-in Wi-Fi and tools to help minimise toner consumption.



## Ready when you are

- A 1-GHz dual-core processor and 512 MB memory drives printing at up to 23 ppm.\*
- The steel frame and durable design stands up to heavy use and harsh environments.
- The long-life fuser and imaging components extend uptime.
- Unison<sup>™</sup> Toner replacement cartridges deliver up to 3,500 colour and 6,000 monochrome pages\*\*.
- Keep printing in black even when a colour toner is empty.

## Colour that keeps saving

- PANTONE<sup>®</sup> calibration, embedded colour sample pages and Lexmark Colour Replacement produce accurate, professional colour output in-house.
- Save toner with a suite of tools that let you choose when and how much colour to print.

#### Input that works

- Reliable, flexible media handling supports cardstock, small media, and envelopes from the main tray or a convenient single-sheet feeder.
- > 251 pages of standard input can grow to 901.

#### Interact with ease

- A 6 cm colour LCD lets you configure, interact and monitor vital system information.
- The front USB port allows walk-up printing from popular file formats without a computer.
- The compact footprint allows flexible placement in more locations.
- Connect easily via Ethernet, USB, Wi-Fi or simple mobile printing options.

## **Full-spectrum security**

- Lexmark's full-spectrum security architecture helps keep your information safe - in the document, on the device and over the network.
- Keypoint Intelligence Buyers Lab honoured Lexmark with a prestigious BLI PaceSetter award for Document Imaging Security\*\*\*.



## **Built for planet earth**

- Energy management features reduce power consumption in active use or sleep mode.
- Standard two-sided printing saves paper.
- Recycle cartridges through the award-winning Lexmark Cartridge Collection Programme (LCCP).

\*Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. \*\*Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information. \*\*\*Award based on Western Europe data



# Lexmark C2425dw



- C2425dw with 6 cm LCD 1 308 x 442 x 421 mm
- 650-sheet duo tray 2 133 x 424 x 416 mm

Adjustable printer stand (not shown) 521 x 653 x 625 mm

Swivel cabinet (not shown) 263 x 476 x 600 mm



Note 1: Supports one optional tray. Note 2: All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at http://www.lexmark.com/publications/furniture\_safety/

© 2018 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. Google Cloud Print is a trademark of Google, Inc. MOPRIA®, the Mopria® Logo<sup>™</sup> and the Mopria® Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. PANTONE®, PANTONE® Goe<sup>TM</sup> and other Pantone, Inc. trademarks are property of Pantone, Inc. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http:// ww.openssl.org/).



Product specifications	Lexmark C2425dw
Printing	
Display	6 cm (2.4-inch) Colour LCD display
Print Speed: Up to <sup>6</sup>	Black: 23 ppm / Colour: 23 ppm
Time to First Page: As fast as / Time to First Page: as fast as	Black: < 10.1 seconds / Colour: < 10.1 seconds
Print Resolution	Black: 1200 x 1200 dpi, 4800 Colour Quality (2400 x 600 dpi) / Colour: 1200 x 1200 dpi, 4800 Colour Quality (2400 x 600 dpi)
Memory / Processor	standard: 512 MB / maximum: 512 MB / Dual Core, 1000 MHz
Hard Disk	Not Available
Recommended Monthly Page Volume <sup>2</sup>	800 - 6,500 Pages
Maximum Monthly Duty Cycle: Up to <sup>3</sup>	75,000 pages per month
Supplies <sup>7</sup>	
Laser Cartridge Yields (up to)1	1,000-page Black and Colour (CMYK) Cartridges, 6,000-page Black Extra High Yield Cartridge, 2,300-page Colour (CMY) High Yield Cartridges, 3,000-page Black High Yield Cartridge, 3,500-page Colour (CMY) Extra High Yield Cartridges
Photoconductor Estimated Yield: Up to <sup>5</sup>	40,000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage
Cartridge(s) Shipping with Product <sup>1</sup>	1,400-page Black Starter Return Programme Toner Cartridge, 750-page Colour (CMY) Starter Return Programme Toner Cartridge
Paper Handling	
Included Paper Handling	250-Sheet Input, 125-Sheet Output Bin, Integrated Duplex, Single-Sheet Manual Feed
Optional Paper Handling	650-Sheet Duo Tray
Paper Input Capacity: Up to	Standard: 250+1 pages 75 gsm bond / Maximum: 900+1 pages 75 gsm bond
Paper Output Capacity: Up to	Standard: 125 pages 75 gsm bond / Maximum: 125 pages 75 gsm bond
Media Types Supported	Card Stock, Envelopes, Paper Labels, Plain Paper, Vinyl Labels, Refer to the Paper & Speciality Media Guide
Media Sizes Supported	10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Hagaki Card, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6
General Information⁴	
Standard Ports	USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), 802.11b/g/n Wireless, Front USB 2.0 Specification Hi-Speed Certified port (Type A)
Optional Network Ports	Marknet N8372 WiFi Option
Noise Level: Operating	Print: 48 dBA
Specified Operating Environment	Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3,048 Metres (10,000 Feet), Temperature: 10 to 32°C (50 to 90°F)
Product Guarantee	4-year guarantee (upon registration)
Size (mm - H x W x D) / Weight	308 x 442 x 421 mm / 21 kg

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions.

<sup>1</sup>Average continuous cartridge yield is stated number of standard pages as listed. Declared yield value in accordance with ISO/IEC 19798. <sup>2</sup>"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup> "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup>Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details. <sup>3</sup>Actual Yield may vary based on other factors such as device speed, pager size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. <sup>9</sup>Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. <sup>7</sup>Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.

# lexmark.co.uk

